


EDLX100

WET | EXPLOSION PROOF | LEED POINTS QUALIFIED



Specifications: Internal

The EDLX100 is 100% reliable, there are no internal parts to fail. It is a non-toxic, non-radioactive low profile exit solution. The EDLX100 is visible at up to 100 feet.

Specifications: External

Construction: ABS plastic with photoluminescent panel. The EDLX100 can be used for high and/or low level installations and has a 25 year life expectancy. It is visible at 100 feet during a blackout condition. The EDLX100 meets current building codes, NFPA Life Safety Code 101 and OSHA requirements; International Building Code 2009/2018; International Fire Code 2009/2018.

Specifications: Electrical

CIRCUIT: Since there is no electricity required, the EDLX100 is a safer signage solution, which saves on maintenance and energy costs.

INSTALLATION: Before installation it must be determined that there is a minimum of 5 Fc of LED, Fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.

Specifications: Mechanical

The EDLX100 series utilizes photoluminescent technology which absorbs and stores ambient light. It is a non-toxic, and non-radioactive low profile emergency lighting solution. The EDLX100 features field adjustable chevrons and is constructed of ABS plastic with photoluminescent panel. The EDLX100 is NON-TOXIC and NON-RADIOACTIVE which eliminates disposal fees.

Warranty

The EDLX100 Series comes with a 10 year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.



Ordering Logic

Series	Face No.	Frame Color	Mounting
EDLX100	P1 (single)	R (red)	UB (universal mounting bracket)
	P2 (double)	G (green)	
		B (black)	

EXAMPLE: EDLX100-P2-B-UB

DESCRIPTION: EDLX100 double face, black frame, photoluminescent letters, universal mounting bracket