

ECOM-4-SM

Surface Mount 4" commercial aluminum posts. Smooth and Fluted Styles in 8', 10', 12', and 14'. Available in Black, White, and Bronze.

Wall Thickness: 0.125 in

Butt Diameter: 4 in

Top Outer Diameter: 3 in

Base Diameter: 10¹/₈ in

Bolt Circle: 8¹/₂ in

Bolt Projection: 4 in



Bolt Size: 3/4 x 12 in

Net Weight: 19 lbs

Luminary Weight: 100 lbs

Tenon Reducer: 2.5"H x 3.0"D

Hand Hole: Standard on 10', 12' and 14' poles. 2" x 4" with Cover (hardware, tamper proof screws, & ground wire included)




Anchor Bolts
 BOLTS & TEMPLATE INCLUDED
 (4 ea.) 3/4" x 18" Galvanized Steel Anchor Bolts
 AASHTO M314-90 Grade 55
 Threaded End Galvanized Per ASTM A153 With (4 ea.) Galvanized Steel Leveling Hex Nuts, (4 ea.) Fastening Hex Nuts, and (8 ea.) Washers
 INSTALL IN REINFORCED CONCRETE (BY OTHERS)



Ordering Information

Part #	Length	Finish	Options
ECOM-4-SM-S Smooth Aluminum Extruded Pole	8= 8' Pole 10= 10' Pole 12= 12' Pole 14= 14' Pole	BLK- Black WHT- White BRZ- Bronze	PB4- Polygon Base Cover SB4- Standard Base Cover HH- Hand Hole (8' pole only, Standard on 10', 12' and 14' Poles)
ECOM-4-SM-F Fluted Aluminum Extruded Pole			



Maximum EPA (ft²)

Length	110 MPH	115 MPH	120 MPH	130 MPH	140 MPH	150 MPH	160 MPH	170 MPH	180 MPH
8'	10.0	9.00	8.50	6.75	5.50	24.75	4.00	3.25	2.75
10'	7.25	6.50	5.75	4.75	3.75	3.00	2.50	2.00	1.50
12'	5.50	4.75	4.25	3.25	2.50	2.00	1.50	1.00	0.75
14'	4.00	3.50	3.00	2.25	1.50	1.00	0.50	0.25	N/A