

## 201 LED Series

### Wrap Around Surface Mounts

#### STANDARD



This surface mounted wrap around unit is designed for use in most commercial, residential, and institutional type applications. The unit provides maximum light output with minimum clearance.

#### Construction:

Housing is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Clear acrylic prismatic wrap around diffuser hinges from either side and snaps on and off for easy maintenance.

#### Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location

#### Mounting


Unit is equipped with knockouts and holes for pendant or surface mounting. This Fixture can be mounted individually or continuous run.



#### WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location

#### DIMENSIONS



max weight= 16lbs/48 32lbs/96"

#### Ordering Guide

E201 LED							
Series	Size	Lumens		Color	Options		
201 LED	2 = 2FT 4 = 4FT 6 = 6FT 8 = 8FT	<u>2FT</u> 3166 (17W) 4350 (24W) 5470 (31W) 6452 (39W)		3K 35K 4K 5K	EMB-I = Internal Emergency driver REFS = Silver Reflector OCC-E = External Occupancy Sensor FR = Frosted Lens over LED Board STEM-MT= Stem Mount		
		<u>4FT</u> 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W)					
		<u>8FT</u> 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W) 13820 (74W) 17280 (96W) 23594 (140W)					

\*0-10v low voltage dimming standard per fixture

\*Higher and custom lumen packages available upon request

\*Call Factory for lumen options of 3FT and 6FT models

Specifications Subject To Change Without Notice