

SML-30XN SERIES

Low Glare LED Wallpack/Surface Mount



Product Description:

This trapezoid full cut-off wall pack is elegant as it is functional. With high performance LEDs and long lasting driver, this fixture provides effective lighting all around. It can be used around factories, restaurants, shopping centers, etc.

Optional Kelvin color* with adder.

Features:

LISTING

UL and CUL listed for wet locations

HOUSING

Die-cast aluminum body

LEDS

New generation LED

FINISH

UV stabilized power coated finish

OPTIONS

Finish - Bronze. Color option with adder

Applications:

	Retails & Supermarkets
	Hotels & Restaurants
	Commercial Buildings
	Offices And Showrooms
	Schools & Colleges



SML-301N



SML-302N






SML-303N



Dimensions:





SML-301N



SML-302N & SML-302N-U/D



SML-303N



Example: SML-30XN Series

Model No.	System Watts	Input Voltage	CRI*	Color Temp*	Finish	Reflector	Option
SML-301N	30W	UNV= 120-277VAC	7=70+	30=3000 K 40= 4000 K 50=5000 K	BR=Bronze	FT = Forward Throw WT= Wide Throw	BLANK = No Sensor
	50W						PC = Photocell (SML-301N & SML-302N Only)
	72W						OC = Occupancy Sensor
SML-302N	30W	UNV= 120-277VAC	7=70+	30=3000 K 40= 4000 K 50=5000 K	BR=Bronze	FT = Forward Throw WT= Wide Throw	EM = Emergency Driver
SML-303N	50W						SS = 10KV Surge
SML-302N-U/D	72W						
SML-302N-U/D	40W						

Performance Data:

Model NO.	System Watts	Lumens**	Efficacy
SML-301N	30W	3811 lm**	131 lm/W**
	50W	6410 lm**	125 lm/W**
	15/30/50/72W	8407 lm**	117 lm/W**
SML-302N/SML-303N	30W	3811 lm**	131 lm/W**
	50W	6410 lm**	125 lm/W**
	15/30/50/72W	8621 lm**	120 lm/W**
SML-302N-U/D	40W	6056 lm**	151 lm/W**

Lumen and Efficacy are based on the highest wattage at 5000K



SML-301N



Forward Throw (FT)




Wide Throw (WT)






Up & Down (U&D)



SML-302N



SML-303N






Quick Mount Guide:

Unlike other fixtures which require more than two people to install, our IMB (Intelligence Mounting Bracket) helps you to save time and money. With its light, small and user friendly, you can install this fixture easily with only one person in a much shorter time. Meanwhile, you can check the leveling by using the integrated level bubble on the mounting bracket. In this competitive industry, we understand the importance of saving you labor cost and time.


A smart tip!



Uninstall the mounting bracket from fixture base plate by unscrewing the 2 hex socket studs.



Remove the mounting bracket.



Level the bracket to intend altitude, install the bracket on the wall.



Lift the fixture up and tilt slightly toward the wall mounted bracket as figure D shown, hook the fixture base plate with the mounting bracket.



Screw tight the bracket and fixture.